



ENER FUEL™

- Cleans Fuel Injectors and Pumps
- Reduces Oxidation to Stabilize Fuel
- Eliminates Water
- Improves Cetane
- Organic Based Formula with No Harmful Alcohols
- Improves Fuel Atomization for More Power, Greater Efficiency, and Reduced Emissions

DIRECTIONS:

- For best results, use every time you fuel, adding contents to fuel tanks prior to fueling. The fueling process will ensure that complete and proper mixing takes place.
- Use 8 ounces for each 250 gallons of fuel (1:4000 treatment ratio).
- First time users can use 8 ounces for each 125 gallons to speed the cleaning process.
- When operating in extreme conditions (marine, high humidity) it is acceptable to use the 8 ounces per 125 gallons dosage on a regular basis.
- Ener Fuel will eliminate its own volume of water.
- In Cold Weather we suggest the use of Polar Flow or Complete Fuel Treatment to prevent fuel from gelling and to improve cold weather operation.

ENERTECH LABS™



Peak Performance Specialists

ENER FUEL™

The Hi-Tech Treatment & Conditioner For Today's Diesel Fuels

Ener Fuel is the All-Season Treatment to Improve Fuel Efficiency, Increase Power, Reduce Emissions, Reduce Engine Wear, Stabilize Fuel, and Eliminate the Harmful Effects of Water in the Fuel.

Ener Fuel is an organic based product that is a powerful fuel system cleaner. It dissolves the gum, varnish, and carbon deposits that distort fuel injector spray patterns and damage delicate injector and pump components. Cleaning these parts allows your engine to operate with all the power and efficiency that the manufacturer designed into it.

- Ener Fuel causes fuel to be atomized better by the fuel injectors for more efficient combustion and reduced emissions.
- Ener Fuel slows the oxidation of fuel, stabilizing it.
- Ener Fuel contains no harmful alcohols that can damage gaskets and seals.
- Ener Fuel chemically removes the water found in all diesel fuel. Water that can corrode metal parts, water that mixes with the sulfur in fuel to create damaging sulfuric acid, water that can freeze in filters and fuel lines, water that supports the growth of spores and bacteria into a thick sticky slime that clogs fuel injectors and plugs fuel filters. By eliminating water, you can prevent all of these problems.
- Ener Fuel will help hold wax in suspension, slowing the growth of crystals that plug filters in cold weather.
- Ener Fuels highly concentrated formula uses only 8 ounces to treat 250 gallons.

With today's Hi-Tech electronically controlled engines, the need to make older equipment last longer, and the difficulty in obtaining fuels that meet the manufacturers requirements, the need for a high quality fuel treatment is more important than ever before.

PACKAGING:

Package Size	Treats	Quantity/Case	Part Number
8 oz. Bottle	250 US Gallons	24 per case	10102
1 US Gallon	4,000 US Gallons	4 per case	10106
5 US Gallon	20,000 US Gallons	1	10107
55 US Gallons	220,000 US Gallons	1	10109
275 US Gallons (tote)	1,100,000 US Gallons	1	10100



For more information please consult the Material Safety Data Sheet for this product. All used and unused product and its containers should be disposed of in accordance with all local, state, and federal regulations. Keep This Product Out Of Reach of Children.

Notice to Purchaser: EnerTech Labs, Inc. provides no warranty of any kind with respect to the product whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

PEAK PERFORMANCE DIESEL ADDITIVES FOR THE: POWER/CHEMICAL; HOME HEATING; TRANSPORTATION; CONSTRUCTION; GOVERNMENT/MILITARY; AND MARINE INDUSTRIES



©EnerTechLabs, Inc. 2003. ENER FUEL is a registered trademark of EnerTech Labs.